

Platinum Wheels

Our wheel coating can be used on painted, powder coated, bare metal aluminum and stainless surfaces, including matt, satin & gloss finishes.

Application instructions

Application must take place above 5C in a well ventilated area, whilst wearing protective gloves. Do not dilute.

Surface condition is important, Ensure it is free of any waxes, oils & dressings, ideally wiped down with our Panel Prep cleaner or IPA mix.

Apply two or three drops onto the lint free V2 applicator provided, apply the coating to the whole wheel evenly, one wheel at a time, larger wheels may need to be coated in sections. Bonding begins immediately, remove excess with a light wipe of a microfibre cloth within a 1-2 minutes, do not leave the coating for longer than 4-5 minutes before wiping. One applicator pad per wheel is recommended.

For maximum durability we recommend two coats, when applying two coats please leave 2 hours before applying the second coat.

Maintenance

This coating requires no special maintenance, typically on a two coat application the coating will last for around two years. Coating durability is improved when the wheels are cleaned only with car shampoo or PH neutral snow foams/citrus degreaser's. Avoid acid wheel cleaners at all costs.

Remove sealant that comes into contact with car paint work, glass, trim and tires immediately.

Caution: Avoid contact with eyes & skin. Do not ingest. Refit cap tightly after use.

